LC TITANIUM STRIP

Low Contact titanium strip with clamp





| LC titanium strip with clamp | | | | | |
|------------------------------|----------|--------------------------------|-----------------|--|--|
| | 7.440.01 | 8.0 mm x 0.4 mm; length 260 mm | 4 047075 128938 | | |

All advantages at a glance

- Low osseointegration due to equal distribution of compressive stress over the bones (compared to cables and wires)
- Studs on the "bone-facing" side prevent the strip from slipping and also reduce osseointegration.
- High level of resistance
- Metal removal much easier than with cables or wires shortens treatment time
- Strip can be retensioned
- Universal use for femur and humerus
- No disruption of periostal blood supply, as proven in extensive studies.



Target group

- The LC titanium strip is intended for adult patients.
- There are no restrictions with regard to selected ethnic groups. The patient clientèle is only limited by anatomical parameters.

Product characteristics

- The side facing the bone has a studded structure over 70 mm of its length.
- The rest of the surface is completely smooth.
- There is a recess at one end for hooking the strip into the passer.
- The clamp for fixing the strip in place is at the opposite end.









Set no. 19.519.00 2 Level view

| Instrumente 10.271.11/65 strip Ø 63 10.271.12/65 strip Ø 43 10.271.12/45 strip Ø 43 10.271.12/45 strip Ø 43 10.271.12/45 strip Ø 43 10.271.12/45 strip Ø 43 10.271.20 Hand 8.0 m 10.271.20 pestk 1/44 10.271.03 power | Imp nm x 0.4 mm; length 260 mm loop instrument; 1/4"-coupling; straight; 5 mm; L 225mm loop instrument; 1/4"-coupling; bevele- 65mm; length 185 mm loop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm stal clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm '-coupling; length 125 mm | ; 1 1 1 | | Container 19.519.10 | perforated autocl.container w.inset f.instruments for titani- um strips | . 1 |
|---|---|---|--|------------------------|---|-----|
| 7.440.01 8.0 m Instrumente 10.271.11/65 strip Ø 63 10.271.12/65 strip Ø 43 10.271.12/45 strip Ø 43 10.271.20 long 10.271.03 pestla 10.271.03 powd | Ioop instrument; 1/4"-coupling; straight; 5 mm; L 225mm Ioop instrument; 1/4"-coupling; bevele- 65mm; length 185 mm Ioop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 100 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 205 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 205 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 205 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 100 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 205 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 205 mm Ioop instrument; 1/4"-coupling; beveled 5 mm; length 100 mm Ioop instrument; 100 mm Ioop ins | 1 1 1 1 1 1 1 1 1 | | | w.inset f.instruments for titani | 1 |
| Instrumente 10.271.11/65 strip 0.271.12/65 strip 0.271.12/65 strip 0.271.12/45 strip 0.271.12/45 strip 0.271.12/45 strip 0.271.12/45 strip 0.271.12/45 strip 0.307.03 Hand 10.271.20 gestland 10.271.03 pestland | loop instrument; 1/4"-coupling; straight; 5 mm; L 225mm loop instrument; 1/4"-coupling; bevele- 65mm; length 185 mm loop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm dle with 1/4" coupling, length 162 mm ersal clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | 1 1 1 1 1 1 1 1 1 | | 19.519.10 | w.inset f.instruments for titani | 1 |
| 10.271.11/65 strip Ø 63 10.271.12/65 strip Ø 43 10.271.11/45 strip Ø 43 10.271.12/45 strip Ø 43 10.271.12/45 strip Ø 43 10.307.03 Hance 10.271.20 gestla 10.271.03 pestla 10.271.03 powd | 5 mm; L 225mm loop instrument; 1/4"-coupling; bevele- 65mm; length 185 mm loop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm stead clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | 1 1 1 1 1 | | | um strips | |
| 10.271.11/65 strip Ø 63 10.271.12/65 strip Ø 43 10.271.11/45 strip Ø 43 10.271.12/45 strip Ø 43 10.271.12/45 strip Ø 43 10.307.03 Hance 10.271.20 gestla 10.271.03 pestla 10.271.03 powd | 5 mm; L 225mm loop instrument; 1/4"-coupling; bevele- 65mm; length 185 mm loop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm stead clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | 1 1 1 1 1 | | | | |
| 10.271.12/65 \$trip 10.271.12/65 \$trip 0.271.11/45 \$trip 0.271.12/45 \$trip 0.271.12/45 \$trip 0.307.03 Hand 10.271.20 \$0.0 10.271.03 pestle 10.271.03 pewd | 5 mm; L 225mm loop instrument; 1/4"-coupling; bevele- 65mm; length 185 mm loop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm stead clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | 1 1 1 1 1 | | | 680 | |
| 10.271.11/45 $d; \emptyset$ 10.271.11/45 $g 4$ 10.271.12/45 $g 4$ 10.307.03 Hanc 10.271.20 $g 0$ 10.271.20 $g 0$ 10.271.03 pest 1/4' 1/4' | 65mm; length 185 mm loop instrument; 1/4"-coupling; straight; 5 mm; length 205 mm loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm dle with 1/4" coupling, length 162 mm ersal clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | 1 ; 1 1 1 | | | 6 | |
| 10.271.12/45 strip Ø 45 10.307.03 Hand 10.271.20 unive 8.0 m 10.271.03 pestk 10.271.05 powe | loop instrument; 1/4"-coupling; beveled 5 mm; length 175 mm dle with 1/4" coupling, length 162 mm ersal clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | ; 1 1 1 | | | | |
| 10.271.20 Ø 43 10.307.03 Hand 10.271.20 8.0 n 10.271.03 pestk 1/4 1/4 | 5 mm; length 175 mm dle with 1/4" coupling, length 162 mm ersal clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | 1 | | | | |
| 10.271.20 unive 8.0 r lengt 10.271.03 pestle 1/4" 10.271.05 power | ersal clamping device for strips up to mm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm |] | | | | |
| 10.271.20 8.0 n lengt 10.271.03 pestle 1/4 10.271.05 power | nm x 0.4 mm/slopes up to Ø 2.0 mm; h 220 mm e for LC titanium strip 8.0 mm x 0.4 mm | | | | | |
| 10.271.03 peste 1/4 | e for LC titanium strip 8.0 mm x 0.4 mm | 1: 1 | And in case of the local division of the loc | | | |
| 10.271.05 powe | | ' 1 | | | | |
| | er cutter for LC titanium strip mm x 0.4 mm; length 260 mm | 1 | | | | |
| 2.975.03 meta | l hammer, weight 300 g | 1 | | | A Million | |
| | | | | | | |

All implants are available on request as non-sterile packed or sterile packed.


Implantation of the strip







Clip into the hook



Pass around





Tighten the screw to clamp



Tighten the strip





Pull into the clamping device



Cut strip




Final result



€€ 0197

LC titanium strip Low Contact titanium strip with clamp KrMo | Edition 04 | 2023-12





Move the tensioner 90°





