

# Straight plates 4.5 as

angle-stable; for screws  $\varnothing$  4.5 mm; stainless steel



Item no. 4.444.08



Item no. 4.445.08









Item no. 4.4445.08









Item no. 4.446.10

| Item no. | Item description | EAN |
|----------|------------------|-----|
|----------|------------------|-----|







### Straight plate 4.5 as bridge 40 – plate thickness 4.0 mm

|          |   |   |
|----------|---|---|
| 4.444.02 | with conical thread and bridge 4.5; 2 holes; 52 x 12 mm; bridge 40; stainless steel   |    |
| 4.444.04 | with conical thread and bridge 4.5; 4 holes; 76 x 12 mm; bridge 40; stainless steel   |    |
| 4.444.06 | with conical thread and bridge 4.5; 6 holes; 100 x 12 mm; bridge 40; stainless steel  |    |
| 4.444.08 | with conical thread and bridge 4.5; 8 holes; 124 x 12 mm; bridge 40; stainless steel  |    |
| 4.444.14 | with conical thread and bridge 4.5; 14 holes; 196 x 12 mm; bridge 40; stainless steel |    |
| 4.444.16 | with conical thread and bridge 4.5; 16 holes; 220 x 12 mm; bridge 40; stainless steel |  |



### Straight plate 4.5 as bridge 40 divergent – plate thickness 4.0 mm

|           |  |   |
|-----------|--|---|
| 4.4445.02 | with conical thread and bridge 4.5; 2 holes; 52 x 12 mm; bridge 40; diverging; stainless steel   |  |
| 4.4445.04 | with conical thread and bridge 4.5; 4 holes; 76 x 12 mm; bridge 40; diverging; stainless steel   |  |
| 4.4445.06 | with conical thread and bridge 4.5; 6 holes; 100 x 12 mm; bridge 40; diverging; stainless steel  |  |
| 4.4445.08 | with conical thread and bridge 4.5; 8 holes; 124 x 12 mm; bridge 40; diverging; stainless steel  |  |
| 4.4445.10 | with conical thread and bridge 4.5; 10 holes; 148 x 12 mm; bridge 40; diverging; stainless steel |  |
| 4.4445.12 | with conical thread and bridge 4.5; 12 holes; 172 x 12 mm; bridge 40; diverging; stainless steel |  |

### Straight plate 4.5 as – plate thickness 4.0 mm

|          |   |   |
|----------|---|---|
| 4.445.04 | with conical thread 4.5; 4 holes; 48 x 12 mm; stainless steel   |  |
| 4.445.05 | with conical thread 4.5; 5 holes; 60 x 12 mm; stainless steel   |  |
| 4.445.06 | with conical thread 4.5; 6 holes; 72 x 12 mm; stainless steel   |  |
| 4.445.08 | with conical thread 4.5; 8 holes; 96 x 12 mm; stainless steel   |  |
| 4.445.12 | with conical thread 4.5; 12 holes; 144 x 12 mm; stainless steel |  |
| 4.445.16 | with conical thread 4.5; 16 holes; 192 x 12 mm; stainless steel |  |

### Straight plate 4.5 as divergent – plate thickness 4.0 mm

|           |   |   |
|-----------|---|---|
| 4.4455.02 | with conical thread 4.5; 2 holes; 24 x 12 mm; screws diverging; stainless steel |  |
| 4.4455.04 | with conical thread 4.5; 4 holes; 48 x 12 mm; screws diverging; stainless steel |  |



Königsee Implantate GmbH  
 OT Aschau | Am Sand 4  
 07426 Allendorf | Germany

Fon +49 36738 498-560  
 Fax +49 36738 498-569




Mail [export@koenigsee-implantate.de](mailto:export@koenigsee-implantate.de)

For further information please visit:  
[www.koenigsee-implantate.com](http://www.koenigsee-implantate.com)



KrMo | Edition 01 | 2020-09  
 All pictured products are CE compliant.

# Straight plates 4.5 as






angle-stable; for screws  $\varnothing$  4.5 mm; stainless steel

| Item no.  | Item description  | EAN  |
|-----------|---|--|
| 4.4455.05 | with conical thread 4.5; 5 holes; 60 x 12 mm; screws diverging; stainless steel   | <br>4 047075 118991 |
| 4.4455.06 | with conical thread 4.5; 6 holes; 72 x 12 mm; screws diverging; stainless steel   | <br>4 047075 119004 |
| 4.4455.08 | with conical thread 4.5; 8 holes; 96 x 12 mm; screws diverging; stainless steel   | <br>4 047075 117482 |
| 4.4455.10 | with conical thread 4.5; 10 holes; 120 x 12 mm; screws diverging; stainless steel | <br>4 047075 119011 |
| 4.4455.12 | with conical thread 4.5; 12 holes; 144 x 12 mm; screws diverging; stainless steel | <br>4 047075 119028 |
| 4.4455.14 | with conical thread 4.5; 14 holes; 168 x 12 mm; screws diverging; stainless steel | <br>4 047075 119035 |
| 4.4455.16 | with conical thread 4.5; 16 holes; 192 x 12 mm; screws diverging; stainless steel | <br>4 047075 119042 |

### Straight plate 4.5 as bridge – plate thickness 5.0 mm

|          |   |  |
|----------|---|--|
| 4.446.10 | with conical thread and bridge 4.5; 10 holes; 148 x 16 mm; bridge 40; stainless steel | <br>4 047075 106837 |
| 4.446.12 | with conical thread and bridge 4.5; 12 holes; 172 x 16 mm; bridge 40; stainless steel | <br>4 047075 106981 |

### Straight plate 4.5 as DC bridge – plate thickness 4.0 mm

|          |   |  |
|----------|---|--|
| 4.473.04 | with conic thread and bridge 4.5; 4 holes; 91 x 12 mm; bridge 55; stainless steel   | <br>4 047075 118922   |
| 4.473.06 | with conic thread and bridge 4.5; 6 holes; 115 x 12 mm; bridge 55; stainless steel  | <br>4 047075 118939  |
| 4.473.08 | with conic thread and bridge 4.5; 8 holes; 139 x 12 mm; bridge 55; stainless steel  | <br>4 047075 118946 |
| 4.473.10 | with conic thread and bridge 4.5; 10 holes; 163 x 12 mm; bridge 55; stainless steel | <br>4 047075 118953 |
| 4.473.12 | with conic thread and bridge 4.5; 12 holes; 187 x 12 mm; bridge 55; stainless steel | <br>4 047075 118960 |