standard; for screws Ø 1.5 mm; Ø 2.0 mm; Ø 2.7 mm; stainless steel







Item no. 4.404.06

Item no. 4.900.05

Item no. 4.307.20







Item no. 4.406.06 Item no. 4.408.08/08

Item no. 4.408.08

Item no. Item description EAN

Straight plate Mini 1.5 – plate thickness 0.9 mm

4.404.04	straight mini plate 1.5;	4 holes;	20 x 4 mm; stainless steel
4.404.06	straight mini plate 1.5;	6 holes;	30 x 4 mm; stainless steel
4.404.07	straight mini plate 1.5;	7 holes;	35 x 4 mm; stainless steel
4.404.08	straight mini plate 1.5;	8 holes;	40 x 4 mm; stainless steel
4.404.15	straight mini plate 1.5;	20 holes;	100 x 4 mm; stainless steel



Adaption plate Mini 2.0 - plate thickness 1.2 mm

4.307.20 mini adaptation-plate 2.0; 20 holes; 100 x 5 mm; stainless steel



Straight plate Mini 2.0 - plate thickness 1.0 mm

4.900.03	straight mini plate with round holes 2.0;	3 holes;	17 x 5 mm; stainless steel
4.900.04	straight mini plate with round holes 2.0;	4 holes;	23 x 5 mm; stainless steel
4.900.05	straight mini plate with round holes 2.0;	5 holes;	29 x 5 mm; stainless steel
4.900.06	straight mini plate with round holes 2.0;	6 holes;	35 x 5 mm; stainless steel
4.900.07	straight mini plate with round holes 2.0;	7 holes;	41 x 5 mm; stainless steel
4.900.08	straight mini plate with round holes 2.0;	8 holes;	47 x 5 mm; stainless steel
4.900.20	straight mini plate with round holes 2.0;	20 holes; 1	19 x 5 mm; stainless steel



Straight plate Mini 2.0 DC bridge 8 - plate thickness 1.0 mm

4.406.02	straight DC-mini plate with bridge 2.0;	2 holes; 12 x 5 mm; bridge 8; stainless steel
4.406.03	straight DC-mini plate with bridge 2.0;	3 holes; 17×5 mm; bridge 8; stainless steel
4.406.04	straight DC-mini plate with bridge 2.0;	4 holes; 22 x 5 mm; bridge 8; stainless steel
4.406.05	straight DC-mini plate with bridge 2.0;	5 holes; 27 x 5 mm; bridge 8; stainless steel
4.406.06	straight DC-mini plate with bridge 2.0;	6 holes; 32 x 5 mm; bridge 8; stainless steel
4.406.07	straight DC-mini plate with bridge 2.0;	7 holes; 37×5 mm; bridge 8; stainless steel
4.406.08	straight DC-mini plate with bridge 2.0;	8 holes; 42×5 mm; bridge 8; stainless steel





Königsee Implantate GmbH OT Aschau | Am Sand 4 07426 Allendorf | Germany

Fon +49 36738 498-560 Fax +49 36738 498-569 For further information please visit: www.koenigsee-implantate.com

Mail export@koenigsee-implantate.de

standard; for screws Ø 1.5 mm; Ø 2.0 mm; Ø 2.7 mm; stainless steel







Item no. 4.408.08/15

Item no. 4.409.06

Item no. 4.410.08/St.







Item no. 4.825.06

Item no. 4.410.06

Item no. 4.410.06/18

Item no.	Item description	EAN
4.406.09 4.406.10 4.406.12 4.406.13 4.406.14 4.406.15 4.406.16	straight DC-mini plate with bridge 2.0; 9 holes; 47 x 5 mm; bridge 8; stainless steel straight DC-mini plate with bridge 2.0; 10 holes; 52 x 5 mm; bridge 8; stainless steel straight DC-mini plate with bridge 2.0; 12 holes; 62 x 5 mm; bridge 8; stainless steel straight DC-mini plate with bridge 2.0; 13 holes; 67 x 5 mm; bridge 8; stainless steel straight DC-mini plate with bridge 2.0; 14 holes; 72 x 5 mm; bridge 8; stainless steel straight DC-mini plate with bridge 2.0; 15 holes; 77 x 5 mm; bridge 8; stainless steel straight DC-mini plate with bridge 2.0; 16 holes; 82 x 5 mm; bridge 8; stainless steel	4 04 7075 105 281
4.406.18	straight DC-mini plate with bridge 2.0; 18 holes; 92 x 5 mm; bridge 8; stainless steel	4 047075 105311

Straight plate Mini 2.0 DC bridge 8 strong – plate thickness 2.0 mm

	11.11
4.408.04/08 straight DC-mini plate with bridge 2.0; 4 holes; 22 x 5 mm; bridge 8; stainless steel	4 0
4.408.05/08 straight DC-mini plate with bridge 2.0; 5 holes; 27 x 5 mm; bridge 8; stainless steel	4 0 4
4.408.06/08 straight DC-mini plate with bridge 2.0; 6 holes; 32 x 5 mm; bridge 8; stainless steel	4 0
4.408.07/08 straight DC-mini plate with bridge 2.0; 7 holes; 37 x 5 mm; bridge 8; stainless steel	4 0
4.408.08/08 straight DC-mini plate with bridge 2.0; 8 holes; 42 x 5 mm; bridge 8; stainless steel	4 0
4.408.09/08 straight DC-mini plate with bridge 2.0; 9 holes; 47 x 5 mm; bridge 8; stainless steel	4 0
4.408.10/08 straight DC-mini plate with bridge 2.0; 10 holes; 52 x 5 mm; bridge 8; stainless steel	ااا ا
4.408.11/08 straight DC-mini plate with bridge 2.0; 11 holes; 57 x 5 mm; bridge 8; stainless steel	4 0
4.408.12/08 straight DC-mini plate with bridge 2.0; 12 holes; 62 x 5 mm; bridge 8; stainless steel	4 0
4.408.13/08 straight DC-mini plate with bridge 2.0; 13 holes; 67 x 5 mm; bridge 8; stainless steel	4 0
4.408.14/08 straight DC-mini plate with bridge 2.0; 14 holes; 72 x 5 mm; bridge 8; stainless steel	4 0
4.408.15/08 straight DC-mini plate with bridge 2.0; 15 holes; 77 x 5 mm; bridge 8; stainless steel	4 0
4.408.16/08 straight DC-mini plate with bridge 2.0; 16 holes; 82 x 5 mm; bridge 8; stainless steel	ا ار



Straight plate Mini 2.0 DC bridge 12 - plate thickness 2.0 mm

4.408.02	straight DC-mini plate with bridge 2.0;	2 holes;	17 x 5 mm; bridge 12; stainless steel
4.408.03	straight DC-mini plate with bridge 2.0;	3 holes;	22 x 5 mm; bridge 12; stainless steel





Königsee Implantate GmbH OT Aschau | Am Sand 4 07426 Allendorf | Germany

Fon +49 36738 498-560 Fax +49 36738 498-569 www.koenigsee-implantate.com

Mail export@koenigsee-implantate.de

For further information please visit:

standard; for screws Ø 1.5 mm; Ø 2.0 mm; Ø 2.7 mm; stainless steel

Item no.	Item description	EAN
4.408.04	straight DC-mini plate with bridge 2.0; 4 holes; 27 x 5 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 3 5 9
4.408.05	straight DC-mini plate with bridge 2.0; 5 holes; 32 x 5 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 3 5 7
4.408.06	straight DC-mini plate with bridge 2.0; 6 holes; 37 x 5 mm; bridge 12; stainless steel	4 04 707 5 105 4 4 1
4.408.07	straight DC-mini plate with bridge 2.0; 7 holes; 42×5 mm; bridge 12; stainless steel	4 04 70 7 5 1 0 5 4 7 2
4.408.08	straight DC-mini plate with bridge 2.0; 8 holes; 47×5 mm; bridge 12; stainless steel	4 04 70 7 5 1 0 5 5 7 1
4.408.09	straight DC-mini plate with bridge 2.0; 9 holes; 52×5 mm; bridge 12; stainless steel	4 04 70 7 5 1 0 5 4 9 6
4.408.10	straight DC-mini plate with bridge 2.0; 10 holes; 57×5 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 5 0 2
4.408.11	straight DC-mini plate with bridge 2.0; 11 holes; 62×5 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 4 0 3
4.408.12	straight DC-mini plate with bridge 2.0; 12 holes; 67×5 mm; bridge 12; stainless steel	4 04 70 7 5 1 0 5 6 7 0
4.408.13	straight DC-mini plate with bridge 2.0; 13 holes; 72×5 mm; bridge 12; stainless steel	4 04 707 5 10 5 5 9 5
4.408.14	straight DC-mini plate with bridge 2.0; 14 holes; 77×5 mm; bridge 12; stainless steel	4 04 70 7 5 1 0 5 6 0 1
4.408.15	straight DC-mini plate with bridge 2.0; 15 holes; 82×5 mm; bridge 12; stainless steel	4 04 707 5 105 526
4.408.16	straight DC-mini plate with bridge 2.0; 16 holes; 87×5 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 5 4 0
4.408.18	straight DC-mini plate with bridge 2.0; 18 holes; 97×5 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 5 5 7
4.408.20	straight DC-mini plate with bridge 2.0; 20 holes; 107×5 mm; bridge 12; stainless steel	4 04 707 5 10 5 69 4

Straight plate Mini 2.0 DC bridge 15 – plate thickness 2.0 mm

0 1	
4.408.05/15	straight DC-mini plate with bridge 2.0; $$ 5 holes; 35×5 mm; bridge 15; stainless steel
4.408.06/15	straight DC-mini plate with bridge 2.0; $$ 6 holes; 40×5 mm; bridge 15; stainless steel
4.408.07/15	straight DC-mini plate with bridge 2.0; 7 holes; 45×5 mm; bridge 15; stainless steel
4.408.08/15	straight DC-mini plate with bridge 2.0; 8 holes; 50 x 5 mm; bridge 15; stainless steel
4.408.09/15	straight DC-mini plate with bridge 2.0; 9 holes; 55×5 mm; bridge 15; stainless steel
4.408.10/15	straight DC-mini plate with bridge 2.0; 10 holes; 60×5 mm; bridge 15; stainless steel
4.408.11/15	straight DC-mini plate with bridge 2.0; 11 holes; 65×5 mm; bridge 15; stainless steel
4.408.12/15	straight DC-mini plate with bridge 2.0; 12 holes; 70×5 mm; bridge 15; stainless steel
4.408.13/15	straight DC-mini plate with bridge 2.0; 13 holes; 75×5 mm; bridge 15; stainless steel
4.408.14/15	straight DC-mini plate with bridge 2.0; 14 holes; 80×5 mm; bridge 15; stainless steel
4.408.15/15	straight DC-mini plate with bridge 2.0; 15 holes; 85×5 mm; bridge 15; stainless steel
4.408.16/15	straight DC-mini plate with bridge 2.0; 16 holes; 90×5 mm; bridge 15; stainless steel



Straight plate Mini 2.0 DC bridge 27 - plate thickness 2.0 mm

4.409.06	straight DC-mini plate with bridge 2.0;	6 holes;	52 x 5 mm; bridge 27; stainless steel
4.409.07	straight DC-mini plate with bridge 2.0;	7 holes;	57 x 5 mm; bridge 27; stainless steel
4.409.08	straight DC-mini plate with bridge 2.0;	8 holes;	62 x 5 mm; bridge 27; stainless steel





Königsee Implantate GmbH OT Aschau | Am Sand 4 07426 Allendorf | Germany

Fon +49 36738 498-560 Fax +49 36738 498-569 For further information please visit: www.koenigsee-implantate.com

standard; for screws \varnothing 1.5 mm; \varnothing 2.0 mm; \varnothing 2.7 mm; stainless steel

Item no.	Item description	EAN
4.409.09	straight DC-mini plate with bridge 2.0; 9 holes; 67 x 5 mm; bridge 27; stainless steel	4 047075 105748
4.409.10	straight DC-mini plate with bridge 2.0; 10 holes; 72 x 5 mm; bridge 27; stainless steel	4 047075 105632
4.409.12	straight DC-mini plate with bridge 2.0; 12 holes; 82 x 5 mm; bridge 27; stainless steel	4 04 707 5 10 5 64 9
4.409.14	straight DC-mini plate with bridge 2.0; 14 holes; 92 x 5 mm; bridge 27; stainless steel	4 047075 105656
4.409.16	straight DC-mini plate with bridge 2.0; 16 holes; 102×5 mm; bridge 27; stainless steel	4 04 707 5 105 663
4.409.18	straight DC-mini plate with bridge 2.0; 18 holes; 112 x 5 mm; bridge 27; stainless steel	4 04 707 5 10 5 7 3 1
Straight plate Mi	ni 2.7 DC bridge 12 arched – plate thickness 2.5 mm	
4.825.02	straight DC-mini plate with bridge 2.7; 2 holes; 20 x 8 mm; bridge 12; stainless steel	4 047075 049189
4.825.03	straight DC-mini plate with bridge 2.7; 3 holes; 28 x 8 mm; bridge 12; stainless steel	4 047075 049202
4.825.04	straight DC-mini plate with bridge 2.7; 4 holes; 36 x 8 mm; bridge 12; stainless steel	4 0 4 7 0 7 5 0 4 9 2 1 9
4.825.05	straight DC-mini plate with bridge 2.7 ; 5 holes; 44×8 mm; bridge 12 ; stainless steel	4 047075 049226
4.825.06	straight DC-mini plate with bridge 2.7; 6 holes; 52×8 mm; bridge 12; stainless steel	4 04 70 7 5 0 4 9 0 5 9
4.825.07	straight DC-mini plate with bridge 2.7; $$ 7 holes; $$ 60 x 8 mm; bridge 12; stainless steel	4 0 4 7 0 7 5 0 4 9 3 1 8
4.825.08	straight DC-mini plate with bridge 2.7; 8 holes; 68 x 8 mm; bridge 12; stainless steel	4 04 707 5 0 4 8 9 0 8
4.825.09	straight DC-mini plate with bridge 2.7; 9 holes; 76×8 mm; bridge 12; stainless steel	4 047075 048977
4.825.10	straight DC-mini plate with bridge 2.7; 10 holes; 84×8 mm; bridge 12; stainless steel	4 047075 048984
4.825.11	straight DC-mini plate with bridge 2.7; 11 holes; 92×8 mm; bridge 12; stainless steel	4 04 70 7 5 0 4 8 9 9 1
4.825.12	straight DC-mini plate with bridge 2.7; 12 holes; 100 x 8 mm; bridge 12; stainless steel	4 04 707 5 0 490 66
4.825.13	straight DC-mini plate with bridge 2.7; 13 holes; 108 x 8 mm; bridge 12; stainless steel	4 047075 049011
4.825.14	straight DC-mini plate with bridge 2.7; 14 holes; 116 x 8 mm; bridge 12; stainless steel	4 0 4 7 0 7 5 0 4 9 0 9 7
4.825.15	straight DC-mini plate with bridge 2.7; 15 holes; 124 \times 8 mm; bridge 12; stainless steel	4 047075 049103
4.825.16	straight DC-mini plate with bridge 2.7; 16 holes; 132 x 8 mm; bridge 12; stainless steel	4 047075 049110
Straight plate Mi	ni 2.7 DC bridge 12 – plate thickness 2.5 mm	
4.410.02	straight DC-mini plate with bridge 2.7; 2 holes; 21 x 8 mm; bridge 12; stainless steel	
4.410.04	straight DC-mini plate with bridge 2.7; 4 holes; 37 x 8 mm; bridge 12; stainless steel	
4.410.05	straight DC-mini plate with bridge 2.7; 5 holes; 45 x 8 mm; bridge 12; stainless steel	4"047075"105755"
4.410.06	straight DC-mini plate with bridge 2.7; 6 holes; 53 x 8 mm; bridge 12; stainless steel	
4.410.07	straight DC-mini plate with bridge 2.7; 7 holes; 61 x 8 mm; bridge 12; stainless steel	4 04 70 7 5 1 10 5 8 1 4
4.410.08	straight DC-mini plate with bridge 2.7; 8 holes; 69 x 8 mm; bridge 12; stainless steel	4 04 70 75 10 5 9 15
4.410.09	straight DC-mini plate with bridge 2.7; 9 holes; 77 x 8 mm; bridge 12; stainless steel	4 04 707 5 10 5 7 9 3
4.410.10	straight DC-mini plate with bridge 2.7; 10 holes; 85×8 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 8 0 9
4.410.11	straight DC-mini plate with bridge 2.7; 11 holes; 93 x 8 mm; bridge 12; stainless steel	4 04 70 7 5 10 5 83 0



Königsee Implantate GmbH OT Aschau | Am Sand 4 07426 Allendorf | Germany

Fon +49 36738 498-560 Fax +49 36738 498-569 For further information please visit: www.koenigsee-implantate.com

standard; for screws Ø 1.5 mm; Ø 2.0 mm; Ø 2.7 mm; stainless steel

Item no.	Item description	EAN
4.410.12	straight DC-mini plate with bridge 2.7; 12 holes; 101 x 8 mm; bridge 12; stainless steel	4 04 707 5 10 5 8 4 7
4.410.13	straight DC-mini plate with bridge 2.7; 13 holes; 109 x 8 mm; bridge 12; stainless steel	4 04 707 5 10 5847
4.410.14	straight DC-mini plate with bridge 2.7; 14 holes; 117×8 mm; bridge 12; stainless steel	4 04 70 7 5 1 0 5 8 6 1
4.410.15	straight DC-mini plate with bridge 2.7; 15 holes; 125 \times 8 mm; bridge 12; stainless steel	######################################
4.410.16	straight DC-mini plate with bridge 2.7; 16 holes; 133 \times 8 mm; bridge 12; stainless steel	4 047075 105724
Straight plate Mi	ni 2.7 DC bridge 16 – plate thickness 2.5 mm	
4.410.02/St.	straight DC-mini plate with bridge 2.7; 2 holes; 25 x 8 mm; bridge 16; stainless steel	4 04 70 7 5 1 1 7 5 6 7
4.410.04/St.	straight DC-mini plate with bridge 2.7; 4 holes; 41 x 8 mm; bridge 16; stainless steel	4 04 707 5 1 1 7 6 4 2
4.410.05/St.	straight DC-mini plate with bridge 2.7; 5 holes; 49 x 8 mm; bridge 16; stainless steel	4 047075 117659
4.410.06/St.	straight DC-mini plate with bridge 2.7; 6 holes; 57 x 8 mm; bridge 16; stainless steel	

4.410.04/St.	straight DC-mini plate with bridge 2.7; 4 holes; 41 x 8 mm; bridge 16; stainless steel
4.410.05/St.	straight DC-mini plate with bridge 2.7 ; 5 holes ; $49 \times 8 \text{ mm}$; bridge 16 ; stainless steel
4.410.06/St.	straight DC-mini plate with bridge 2.7 ; 6 holes; 57×8 mm; bridge 16 ; stainless steel
4.410.07/St.	straight DC-mini plate with bridge 2.7 ; 7 holes ; $65 \times 8 \text{ mm}$; bridge 16 ; stainless steel
4.410.08/St.	straight DC-mini plate with bridge 2.7; 8 holes; 73 x 8 mm; bridge 16; stainless steel
4.410.09/St.	straight DC-mini plate with bridge 2.7; 9 holes; 81 x 8 mm; bridge 16; stainless steel
4.410.10/St.	straight DC-mini plate with bridge 2.7; 10 holes; 89 x 8 mm; bridge 16; stainless steel
4.410.11/St.	straight DC-mini plate with bridge 2.7; 11 holes; 97 x 8 mm; bridge 16; stainless steel
4.410.12/St.	straight DC-mini plate with bridge 2.7; 12 holes; 105 x 8 mm; bridge 16; stainless steel
4.410.13/St.	straight DC-mini plate with bridge 2.7; 13 holes; 113 x 8 mm; bridge 16; stainless steel
4.410.14/St.	straight DC-mini plate with bridge 2.7; 14 holes; 121 x 8 mm; bridge 16; stainless steel
4.410.15/St.	straight DC-mini plate with bridge 2.7 ; 15 holes; 129×8 mm; bridge 16 ; stainless steel
4.410.16/St.	straight DC-mini plate with bridge 2.7; 16 holes; 137×8 mm; bridge 16; stainless steel



Straight plate Mini 2.7 DC bridge 18 - plate thickness 2.5 mm

4.410.06/18	straight DC-mini plate with bridge 2.7; 6 holes; 59 x 8 mm; bridge 18; stainless steel
4.410.07/18	straight DC-mini plate with bridge 2.7; 7 holes; 67 x 8 mm; bridge 18; stainless steel
4.410.08/18	straight DC-mini plate with bridge 2.7; 8 holes; 75 x 8 mm; bridge 18; stainless steel





Königsee Implantate GmbH OT Aschau | Am Sand 4 07426 Allendorf | Germany

Fon +49 36738 498-560 Fax +49 36738 498-569 For further information please visit: www.koenigsee-implantate.com