

Straight plates 3.5























standard; for screws Ø 3.5 mm; stainless steel



Item no. 4.820.06



Item no. 4.822.08/SA

Item no.	Item description	EAN
Straight plate 3.5 DC bridge 19 – plate thickness 3.2 mm		
4.820.02	Straight DC-plate with bridge 3.5; 2 holes; 26 x 10 mm; bridge 19; stainless steel	
4.820.03	Straight DC-plate with bridge 3.5; 3 holes; 38 x 10 mm; bridge 19; stainless steel	
4.820.04	Straight DC-plate with bridge 3.5; 4 holes; 50 x 10 mm; bridge 19; stainless steel	
4.820.05	Straight DC-plate with bridge 3.5; 5 holes; 62 x 10 mm; bridge 19; stainless steel	
4.820.06	Straight DC-plate with bridge 3.5; 6 holes; 74 x 10 mm; bridge 19; stainless steel	
4.820.07	Straight DC-plate with bridge 3.5; 7 holes; 86 x 10 mm; bridge 19; stainless steel	
4.820.08	Straight DC-plate with bridge 3.5; 8 holes; 98 x 10 mm; bridge 19; stainless steel	
4.820.09	Straight DC-plate with bridge 3.5; 9 holes; 110 x 10 mm; bridge 19; stainless steel	
4.820.10	Straight DC-plate with bridge 3.5; 10 holes; 122 x 10 mm; bridge 19; stainless steel	
4.820.11	Straight DC-plate with bridge 3.5; 11 holes; 134 x 10 mm; bridge 19; stainless steel	
4.820.12	Straight DC-plate with bridge 3.5; 12 holes; 146 x 10 mm; bridge 19; stainless steel	
4.820.13	Straight DC-plate with bridge 3.5; 13 holes; 158 x 10 mm; bridge 19; stainless steel	
4.820.14	Straight DC-plate with bridge 3.5; 14 holes; 170 x 10 mm; bridge 19; stainless steel	
4.820.15	Straight DC-plate with bridge 3.5; 15 holes; 182 x 10 mm; bridge 19; stainless steel	
4.820.16	Straight DC-plate with bridge 3.5; 16 holes; 194 x 10 mm; bridge 19; stainless steel	
4.820.17	Straight DC-plate with bridge 3.5; 17 holes; 206 x 10 mm; bridge 19; stainless steel	
4.820.18	Straight DC-plate with bridge 3.5; 18 holes; 218 x 10 mm; bridge 19; stainless steel	
Straight plate 3.5 DC bridge 25 – plate thickness 3.2 mm		
4.820.06S	Straight DC-plate with bridge 3.5; 6 holes; 80 x 10 mm; bridge 25; stainless steel	
Straight plate 3.5 DC bridge 19 strong – plate thickness 4.0 mm		
4.822.06	Straight DC-plate with bridge 3.5; 6 holes; 74 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.07	Straight DC-plate with bridge 3.5; 7 holes; 86 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.08	Straight DC-plate with bridge 3.5; 8 holes; 98 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.09	Straight DC-plate with bridge 3.5; 9 holes; 110 x 10 mm; bridge 19; extra strong; stainless steel	



Königsee Implantate GmbH
 OT Aschau | Am Sand 4
 07426 Allendorf | Germany

Fon +49 36738 498-560
 Fax +49 36738 498-569

Mail export@koenigsee-implantate.de

For further information please visit:
www.koenigsee-implantate.com




KrMo | Edition 02 | 2020-09
 All pictured products are CE compliant.

Straight plates 3.5

standard; for screws Ø 3.5 mm; stainless steel

Item no.	Item description	EAN
4.822.10	Straight DC-plate with bridge 3.5; 10 holes; 122 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.11	Straight DC-plate with bridge 3.5; 11 holes; 134 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.12	Straight DC-plate with bridge 3.5; 12 holes; 146 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.13	Straight DC-plate with bridge 3.5; 13 holes; 158 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.14	Straight DC-plate with bridge 3.5; 14 holes; 170 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.16	Straight DC-plate with bridge 3.5; 16 holes; 194 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.18	Straight DC-plate with bridge 3.5; 18 holes; 218 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.20	Straight DC-plate with bridge 3.5; 20 holes; 242 x 10 mm; bridge 19; extra strong; stainless steel	
4.822.22	Straight DC-plate with bridge 3.5; 22 holes; 266 x 10 mm; bridge 19; extra strong; stainless steel	

Straight plate 3.5 DC bridge 45 strong – plate thickness 4.0 mm

4.822.08/SA	Straight DC-plate with bridge 3.5; 8 holes; 126 x 10 mm; bridge 45; extra strong; stainless steel	
4.822.09/SA	Straight DC-plate with bridge 3.5; 9 holes; 138 x 10 mm; bridge 45; extra strong; stainless steel	
4.822.10/SA	Straight DC-plate with bridge 3.5; 10 holes; 150 x 10 mm; bridge 45; extra strong; stainless steel	
4.822.12/SA	Straight DC-plate with bridge 3.5; 12 holes; 174 x 10 mm; bridge 45; extra strong; stainless steel	