

## All the advantages at a glance

- Plate thickness of only 1.8 mm and significantly flattened at the head, ensuring excellent protection of the flexor tendons
- Additional threaded holes in the head make the fixation of multiple small fragments easier
- Safe handling of the radial styloid process with up to 3 screws
- Outstanding anatomical plate design
- Suture fixation holes in the plate enable re-fixation of the pronator quadratus muscle
- Use of 1.8 mm variable angle-stable support pins possible
- Plate opening for the reduction of intra-articular fragments
- Variable angle-stable holes enable the optional use of standard screws or Ø 2.4 mm angle-stable cortical screws with TOBI® drive
- The screwdriver's self-retaining function improves the user-friendliness of the system
- Redesigned screwdriver handle for more comfortable use

## Contact us

If we have piqued your interest in the **RADIUS PLATE 2.4**, please contact us or your sales representative.



### Königsee Implantate GmbH

OT Aschau | Am Sand 4  
07426 Allendorf  
Germany

export@koenigsee-implantate.de  
+ 49 36738 498 - 560



## RADIUSPLATE 2.4

Distal Radiusplate 2.4 vas  
with TOBI®-Drive



TOBI



[www.koenigsee-implantate.de](http://www.koenigsee-implantate.de)

Copyright © Königsee Implantate GmbH  
SiZi | Edition 02 | 2024-03



**Königsee**  
Implantate

## Target group

The treatment with a variable angle stable radius plate 2.4 is for adult patients.

## Properties

- Various plate widths for individual treatment
- Variable angle stable screw joint enables fragment-specific fixation
- Elongated holes in the plates enable alignment on the radius
- Rounded atraumatic plate design

## Available plates

### Variable angle-stable radius plate, narrow



- 7 holes in the distal plate region
- 2 - 12 holes in the shaft area



- Width: 23 mm
- Lengths: 46 - 131 mm
- Left and right
- Titanium

### Variable angle-stable radius plate, broad



- 9 holes in the distal plate region
- 2 - 12 holes in the shaft area



- Width: 28 mm
- Lengths: 46 - 131 mm
- Left and right
- Titanium

## Set Radius plate 2.4 vas with TOBI® drive



OP: Set radius plate 2.4 with TOBI® drive

### Angle stable cortical screw

#### TOBI

- Ø 2.4 mm
- Self tapping
- Available lengths: 10 - 28 mm
- Anodised surface
- With TOBI® drive
- Titanium

### Angle stable pins



#### TOBI

- Ø 1.8 mm
- Lengths: 16 - 28 mm
- Anodised surface
- With TOBI® drive
- Titanium

### Standard cortical screw

#### TOBI

- Ø 2.4 mm
- Self tapping
- Lengths: 12 - 20 mm
- Anodised surface
- With TOBI® drive
- Titanium



**Note:** For the screws with TOBI® drive B8, only the corresponding screwdriver with the appropriate blade for TOBI® drive B8 (Item no. 2.9286.08) may be used.

