

Cannulated screw

steel

non-sterile packaging / sterile packaging



Art.-Nr. 2.520.55



Art.-Nr. 2.523.45



Art.-Nr. 2.414.50



Art.-Nr. 2.424.45

Item no.	EAN	Item description	Item no. sterile	EAN sterile
Cannulated screw 6.5 cann. 2.2 thread 16 st bt sd				
2.520.30		Cannulated screw; Ø 6.5 mm x 30 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.30	
2.520.35		Cannulated screw; Ø 6.5 mm x 35 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.35	
2.520.40		Cannulated screw; Ø 6.5 mm x 40 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.40	
2.520.45		Cannulated screw; Ø 6.5 mm x 45 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.45	
2.520.50		Cannulated screw; Ø 6.5 mm x 50 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.50	
2.520.55		Cannulated screw; Ø 6.5 mm x 55 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.55	
2.520.60		Cannulated screw; Ø 6.5 mm x 60 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.60	
2.520.65		Cannulated screw; Ø 6.5 mm x 65 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.65	
2.520.70		Cannulated screw; Ø 6.5 mm x 70 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.70	
2.520.75		Cannulated screw; Ø 6.5 mm x 75 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.75	
2.520.80		Cannulated screw; Ø 6.5 mm x 80 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.80	
2.520.85		Cannulated screw; Ø 6.5 mm x 85 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.85	
2.520.90		Cannulated screw; Ø 6.5 mm x 90 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.90	
2.520.95		Cannulated screw; Ø 6.5 mm x 95 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.95	



Cannulated screw

steel

non-sterile packaging / sterile packaging

Item no.	EAN	Item description	Item no. sterile	EAN sterile
2.520.100		Cannulated screw; Ø 6.5 mm x 100 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.100	
2.520.105		Cannulated screw; Ø 6.5 mm x 105 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.105	
2.520.110		Cannulated screw; Ø 6.5 mm x 110 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.110	
2.520.115		Cannulated screw; Ø 6.5 mm x 115 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.115	
2.520.120		Cannulated screw; Ø 6.5 mm x 120 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.120	
2.520.125		Cannulated screw; Ø 6.5 mm x 125 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.125	
2.520.130		Cannulated screw; Ø 6.5 mm x 130 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.130	
2.520.135		Cannulated screw; Ø 6.5 mm x 135 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.135	
2.520.140		Cannulated screw; Ø 6.5 mm x 140 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.520.140	



Cannulated screw 6.5 cann. 2.2 thread 32 st bt sd

2.523.45		Cannulated screw; Ø 6.5 mm x 45 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.45	
2.523.50		Cannulated screw; Ø 6.5 mm x 50 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.50	
2.523.55		Cannulated screw; Ø 6.5 mm x 55 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.55	
2.523.60		Cannulated screw; Ø 6.5 mm x 60 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.60	
2.523.65		Cannulated screw; Ø 6.5 mm x 65 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.65	
2.523.70		Cannulated screw; Ø 6.5 mm x 70 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.70	
2.523.75		Cannulated screw; Ø 6.5 mm x 75 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.75	







Cannulated screw

steel

non-sterile packaging / sterile packaging

Item no.	EAN	Item description	Item no. sterile	EAN sterile
2.523.80		Cannulated screw; Ø 6.5 mm x 80 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.80	
2.523.85		Cannulated screw; Ø 6.5 mm x 85 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.85	
2.523.90		Cannulated screw; Ø 6.5 mm x 90 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.90	
2.523.95		Cannulated screw; Ø 6.5 mm x 95 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.95	
2.523.100		Cannulated screw; Ø 6.5 mm x 100 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.100	
2.523.105		Cannulated screw; Ø 6.5 mm x 105 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.105	
2.523.110		Cannulated screw; Ø 6.5 mm x 110 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.110	
2.523.115		Cannulated screw; Ø 6.5 mm x 115 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.115	
2.523.120		Cannulated screw; Ø 6.5 mm x 120 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.120	
2.523.125		Cannulated screw; Ø 6.5 mm x 125 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.125	
2.523.130		Cannulated screw; Ø 6.5 mm x 130 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.130	
2.523.135		Cannulated screw; Ø 6.5 mm x 135 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.135	
2.523.140		Cannulated screw; Ø 6.5 mm x 140 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.523.140	



































Cannulated screw 7.0 cann. 2.2 thread 16 st bt sd

2.414.30		Cannulated screw; Ø 7.0 mm x 30 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.30	
2.414.35		Cannulated screw; Ø 7.0 mm x 35 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.35	
2.414.40		Cannulated screw; Ø 7.0 mm x 40 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.40	

Cannulated screw

steel































non-sterile packaging / sterile packaging

Item no.	EAN	Item description	Item no. sterile	EAN sterile
2.414.45		Cannulated screw; Ø 7.0 mm x 45 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.45	
2.414.50		Cannulated screw; Ø 7.0 mm x 50 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.50	
2.414.55		Cannulated screw; Ø 7.0 mm x 55 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.55	
2.414.60		Cannulated screw; Ø 7.0 mm x 60 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.60	
2.414.65		Cannulated screw; Ø 7.0 mm x 65 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.65	
2.414.70		Cannulated screw; Ø 7.0 mm x 70 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.70	
2.414.75		Cannulated screw; Ø 7.0 mm x 75 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.75	
2.414.80		Cannulated screw; Ø 7.0 mm x 80 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.80	
2.414.85		Cannulated screw; Ø 7.0 mm x 85 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.85	
2.414.90		Cannulated screw; Ø 7.0 mm x 90 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.90	
2.414.95		Cannulated screw; Ø 7.0 mm x 95 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.95	
2.414.100		Cannulated screw; Ø 7.0 mm x 100 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.100	
2.414.105		Cannulated screw; Ø 7.0 mm x 105 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.105	
2.414.110		Cannulated screw; Ø 7.0 mm x 110 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.110	
2.414.115		Cannulated screw; Ø 7.0 mm x 115 mm; thread length 32 mm; internal Ø 2.2 mm; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.115	
2.414.120		Cannulated screw; Ø 7.0 mm x 120 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.120	
2.414.125		Cannulated screw; Ø 7.0 mm x 125 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.125	

Cannulated screw

steel










non-sterile packaging / sterile packaging

Item no.	EAN	Item description	Item no. sterile	EAN sterile
2.414.130		Cannulated screw; Ø 7.0 mm x 130 mm; thread length 16 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.414.130	
Cannulated screw 7.0 cann. 2.2 thread 32 st bt sd				
2.424.40		Cannulated screw; Ø 7.0 mm x 40 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.40	
2.424.45		Cannulated screw; Ø 7.0 mm x 45 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.45	
2.424.50		Cannulated screw; Ø 7.0 mm x 50 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.50	
2.424.55		Cannulated screw; Ø 7.0 mm x 55 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.55	
2.424.60		Cannulated screw; Ø 7.0 mm x 60 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.60	
2.424.65		Cannulated screw; Ø 7.0 mm x 65 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.65	
2.424.70		Cannulated screw; Ø 7.0 mm x 70 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.70	
2.424.75		Cannulated screw; Ø 7.0 mm x 75 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.75	
2.424.80		Cannulated screw; Ø 7.0 mm x 80 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.80	
2.424.85		Cannulated screw; Ø 7.0 mm x 85 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.85	
2.424.90		Cannulated screw; Ø 7.0 mm x 90 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.90	
2.424.95		Cannulated screw; Ø 7.0 mm x 95 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.95	
Cannulated screw 7.0 cann. 2.2 thread 32 st bt sd				
2.424.100		Cannulated screw; Ø 7.0 mm x 100 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.100	
2.424.105		Cannulated screw; Ø 7.0 mm x 105 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.105	

Cannulated screw

steel

non-sterile packaging / sterile packaging

Item no.	EAN	Item description	Item no. sterile	EAN sterile
2.424.110		Cannulated screw; Ø 7.0 mm x 110 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.110	
2.424.115		Cannulated screw; Ø 7.0 mm x 115 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.115	
2.424.120		Cannulated screw; Ø 7.0 mm x 120 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.120	
2.424.125		Cannulated screw; Ø 7.0 mm x 125 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.125	
2.424.130		Cannulated screw; Ø 7.0 mm x 130 mm; thread length 32 mm; internal Ø 2.2 mm; self drilling; back tapping; self tapping; internal hexagon 3.5 mm; stainless steel	S2.424.130	